

Product datasheet

uvex 1 x-tended support 8516 1-3

Safety shoe DIN EN ISO 20345:2022+A1:2024 S3L FO SC SR Sizes: 35 - 52 | Width: 10, 11, 12











AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (SR)
- oil- and fuel resistant (FO)
- free of silicones, plasticisers and other substances that interfere with wetting agents





FEATURES	
Upper material	 breathable microvelour (clima zone) water-repellent (WPA) suitable for people allergic to chrome
Lining material	textile distance mesh lining for comfortable foot climate
Fastening	elastic laces
heel basket	foamed heel basket for additional stability in the shoe
Comfort	soft padding on collar
	 sizes 35-40 have been produced using a women's last
	dust tongue
Insock	removable comfortable insock
PROTECTIVE FEATUR	RES
Toe cap	metal-free protective toe cap
Penetration resistance	metal-free, textile penetration resistance
Scuffcap	 out of PU for additional protection of the upper material (SC)
CERTIFICATES	
uvex medicare+	 certified for orthopaedic insocks and shoe adjustments according to the description in DGUV 112-191
100% vegan	certified free from animal ingredients and products
	 additional protection for people with allergies and intolerances
ESD	protection against electrostatic charge according to EN
	61340-4-3 und EN 61340-5-1
SUSTAINABILITY	
Recycled/sustainable materials	removable insock made wholly or partly from recycled
	 materials free from harmful substances in accordance with the
	uvex restricted substances list
ACCESORIES/ SPARE	
Replacement insock	• 9534 7-0
tune-up insock	• low 95281
	• medium 95282
	• high 95283
Laces	• black 9599920
Elastic laces	• 9591000