

Product datasheet

uvex 1 x-tended support 8517 1-3

Safety boot DIN EN ISO 20345:2022+A1:2024 S3L FO SC SR
Sizes: 35 - 52 | Width: 10, 11, 12



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Dual-density polyurethane sole



- PU outsole
- shock-absorbing PU midsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES	
Upper material	<ul style="list-style-type: none"> • breathable microvelour (clima zone) • water-repellent (WPA) • suitable for people allergic to chrome • textile distance mesh lining for comfortable foot climate • laces • foamed heel basket for additional stability in the shoe • soft padding on collar • sizes 35-40 have been produced using a women's last • dust tongue • removable comfortable insock • metal-free
Lining material	
Fastening	
heel basket	
Comfort	
Insock	
Furthermore	
PROTECTIVE FEATURES	
Toe cap	<ul style="list-style-type: none"> • metal-free protective toe cap • metal-free, textile penetration resistance • out of PU for additional protection of the upper material (SC)
Penetration resistance	
Scuffcap	
CERTIFICATES	
uvex medicare+	<ul style="list-style-type: none"> • certified for orthopaedic insocks and shoe adjustments according to the description in DGUV 112-191 • certified free from animal ingredients and products • additional protection for people with allergies and intolerances • protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1
100% vegan	
ESD	
SUSTAINABILITY	
Recycled/sustainable materials	<ul style="list-style-type: none"> • removable insock made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list
ACCESORIES/ SPARE PARTS	
Replacement insock	<ul style="list-style-type: none"> • 9534 7-0 • low 95281 • medium 95282 • high 95283 • black 9599921
tune-up insock	
Laces	